

## M68-


Plug:	<b>BIPOLAR</b> <b>2 poles</b>
Rated voltage:	<b>250 V</b>
Rated current:	<b>2,5 A</b>
Insulation class:	<b>II</b>
Type of clamps for cables connection:	<b>CRIMPED CLAMPS</b>
Cable exit:	<b>AXIAL</b>
Protection degree:	<b>IP20</b>
In conformity to the standards:	<b>EN 60320</b>



**M68A-**: plug M68- with inner female contacts diameter 2,28 mm.  
**M68B-**: plug M68- with inner female contacts diameter 2,75 mm.

• Table of the cables connected to the plug:

Insulation	Shape	Sections	Temperature	Type	cod./page
PVC + PVC TRANSPARENT	flat	2 x 0,75 mm <sup>2</sup>	T70°C	FRDR	RSP7T (page 9057)
PVC + PVC TRANSPARENT	flat	2 x 0,75 mm <sup>2</sup>	T70°C	FRDR	RBP7T (page 9056)
FEP + PVC TRANSPARENT	flat	2 x 0,75 mm <sup>2</sup>	T70°C (T180°C cores)	FR5FDR	BSP7T (page 9063)
FEP + PVC TRANSPARENT	round	2 x 0,75 mm <sup>2</sup>	T70°C (T180°C cores)	FR5FOR	BS27T (page 9063)
FEP + PVC B - N	flat	2 x 0,75 mm <sup>2</sup>	T70°C	H03WH2-F	RRP7- (page 9053)
PVC + PVC B - N	flat	2 x 0,75 mm <sup>2</sup>	T90°C	H03V2/H2-F	RHP7- (page 9052)



- Body in injected thermoplastic PVC.  
Tinned brass contacts.

• Table of the available colours:

**T** = transparent

**B** = white

**N** = black

- Other colours on request.

